

## CS5560 Chlorine Dioxide Sensor (Potentiostatic)

### Specifications

Measuring Range: 0 - 20.00 mg/L

Temperature Range: 0 - 50°C

Double liquid junction, annular liquid junction

Temperature sensor: standard no, optional

Housing/dimensions:

glass, 120mm\*Φ12.7mm

Wire: wire length 5m or agreed, terminal

Measurement method: tri-electrode method

Connection thread: PG13.5

This electrode is used with a flow cell.



### Order No.

Name	Details	No.
	None	N0
	NTC10K	N1
	NTC2.252K	N2
Temperature sensor	PT100	P1
	PT1000	P2
	5m	m5
Cable Length	10m	m10
	15m	m15
	20m	m20
	boring tin	A1
Cable connection	Y	A2
	Pin	A3
	aviation plug	HK

<b>Model No.</b>	<b>CS5560</b>
<b>Measurement method</b>	Tri-electrode method
<b>Measure material</b>	Double liquid junction,annular liquid junction
<b>Housing material/Dimensions</b>	PP, Glass, 120mm*Φ 12.7mm
<b>Waterproof grade</b>	IP68
<b>Measurement range</b>	0 - 20.00 mg/L
<b>Accuracy</b>	±0.05mg/L;
<b>Pressure resistance</b>	≤0.3Mpa
<b>Temperature compensation</b>	None or Customize NTC10K
<b>Temperature range</b>	0-50℃
<b>Calibration</b>	Sample calibration
<b>Connection methods</b>	4 core cable
<b>Cable length</b>	Standard 5m cable, can be extended to 100m
<b>Installation thread</b>	PG13.5
<b>Application</b>	Tap water, disinfectant fluid, etc.