

CS7920D Online Flow-through Turbidity Sensor



The principle of the turbidity sensor is based on the combined infrared absorption and scattered light method. The ISO7027 method can be used to continuously and accurately determine the turbidity value. According to ISO7027 infrared double-scattering light technology is not affected by chromaticity to determine the sludge concentration value. The self-cleaning function can be selected according to the use environment. Stable data, reliable performance; built-in self-diagnosis function to ensure accurate data; simple installation and calibration.

The electrode body is made of POM, which is corrosion-resistant and more durable. The seawater version can be plated with titanium, which also performs well under strong corrosion.

IP68 waterproof design, can be used for input measurement. Real-time online recording of Turbidity/MLSS/SS, temperature data and curves, compatible with all water quality meters of our company.

5-400NTU-2000NTU-4000NTU, a variety of measuring ranges are available, suitable for different working conditions, the measurement accuracy is less than $\pm 5\%$ of the measured value.

Typical application:

Turbidity monitoring of water from waterworks, water quality monitoring of municipal pipeline network; industrial process water quality monitoring, circulating cooling water, activated carbon filter effluent, membrane filtration effluent, etc.

Technical parameters:

| | |
|------------------------------|--|
| Model No. | CS7920D/CS7921D/CS7930D |
| Power/Outlet | 9~36VDC/RS485 MODBUS RTU |
| Measurement mode | 90° IR scattered light method |
| Dimensions | 50mm*223mm |
| Housing material | POM |
| Waterproof rating | IP68 |
| Measurement range | 5-400 NTU/2000NTU/4000NTU |
| Measurement accuracy | ±5% or 0.5NTU, whichever is greater |
| Pressure resistance | ≤0.3Mpa |
| Measuring temperature | 0-45℃ |
| Calibration | Standard liquid calibration, water sample calibration |
| Cable length | Standard 10m, can be extended to 100m |
| Thread | Flow-through |
| Application | General applications, municipal pipeline network; industrial process water quality monitoring, circulating cooling water, activated carbon filter effluent, membrane filtration effluent, etc. |